

SRS ViVA 1 special F eco



Special High Performance Low Friction Engine Oil

June 2019

Characteristics

SRS ViVA 1 special F eco is a high performance low friction 5W-20 engine oil based on modern synthetic technology.

Excellent low temperature flow characteristics protect optimal the engine during the cold starting. Extreme loads and high temperatures are safely handled under all operating conditions. It ensures very high wear protection and lower friction losses (HTHS < 3.5 mPa s). SRS ViVA 1 special F eco contributes through its high fuel economy and reduction of emissions to protect the environment.

Application

SRS ViVA 1 special F eco is a top quality for passenger car gasoline Ford EcoBoost engines of the Ford specification WSS-M2C948-B and corresponds to the earlier ACEA A1/B1.

Specification

- SAE Grade 5W-20
- API SN
- ACEA C5

Approvals

- Ford WSS-M2C948-B
- Jaguar Land Rover STJLR.03.5004

SRS ViVA 1 special F eco is a product of the H&R ChemPharm GmbH.

Typical Data	Test Method	SRS ViVA 1 special F eco
SAE Grade	SAE J 300	5W-20
Density at 15°C	DIN 51 757	0.851
Dyn. Viscosity at -30°C (CCS)	ASTM D 5293	3,980
Kin. Viscosity at 40°C	DIN EN ISO 3104	40.7
Kin. Viscosity at 100°C	DIN EN ISO 3104	7.8
Viscosity Index (VI)	DIN ISO 2909	166
Flash Point COC	DIN ISO 2592	230
Pour Point	DIN ISO 3016	-36
Total Base Number	DIN ISO 3771	8.1

The above values may vary within the commercial limits.

Made in Germany

